

Amendments to the Drawings:

The attached replacement drawing sheet makes changes to Fig. 4 and replaces the original sheet with Fig. 4.

Attachment: Replacement Sheet

REMARKS


Claims 1-16 are pending. Claims 1-5 are amended and claims 6-16 are added. A marked-up copy and substitute specification are attached hereto. The substitute specification contains no new matter. Further, an amended Abstract is attached. Lastly, Fig. 4 is corrected to reduce the size of the line marking the truncation of a part so that it is not misunderstood as a reference line leading to (C1).

It is respectfully requested the Amendment be entered prior to taking the application up for examination. On the basis of the Amendment it is respectfully submitted that this application is in condition for allowance.

In view of the foregoing, it is respectfully submitted that this application is in condition for allowance. Favorable reconsideration and prompt allowance of claims 1-16 are earnestly solicited.

Should the Examiner believe that anything further would be desirable in order to place this application in even better condition for allowance, the Examiner is invited to contact the undersigned at the telephone number set forth below.

Respectfully submitted,



James A. Oliff
Registration No. 27,075

Robert A. Miller
Registration No. 32,771

JAO:RAM/crh

Attachments:

Marked-up Specification
Substitute Specification
Replacement Sheet
Amended Abstract

Date: December 14, 2005

OLIFF & BERRIDGE, PLC
P.O. Box 19928
Alexandria, Virginia 22320
Telephone: (703) 836-6400

<p>DEPOSIT ACCOUNT USE AUTHORIZATION Please grant any extension necessary for entry; Charge any fee due to our Deposit Account No. 15-0461</p>
--

ABSTRACT

A stator manufacturing device including a winding unit for forming a winding coil ~~consisting~~ made up of a plurality of unipolar coils formed by winding wire, an insertion unit for receiving the winding coil from the winding unit and inserting the winding coil into a stator core, a shaping unit for shaping an outline of the winding coil that has been inserted into the stator core, and a transfer unit that is movable towards the insertion unit and the shaping unit, ~~characterized in~~ such that, in a state of holding the stator core, the transfer unit, by relatively moving to the insertion unit, moves the winding coil into a position for insertion into the stator core, and, by ~~relatively moving~~ relative to the shaping unit, forms an outline of the winding coil.

10/560775

New U.S. National Stage of PCT/JP04/013729
Filed December 14, 2005

IAP20 RECEIVED 14 DEC 2005

MARKED-UP COPY OF SUBSTITUTE SPECIFICATION

This application is the U.S. National Stage
of PCT/JP2004/013729, filed September 21, 2004,
which claims priority from JP 2003-332333,
filed September 24, 2003, the disclosures
of which are incorporated herein in their
entireties by reference.

MARKED-LP Copy

10/560775

SPECIFICATION

JAP20

14 DEC 2005

STATOR MANUFACTURING DEVICE

TECHNICAL FIELD

BACKGROUND

5 [0001] This invention ^{disclosure} generally relates to a stator manufacturing device for manufacturing a stator by arranging a winding coil, which is formed by winding wire, in a stator core.

BACKGROUND ART

10 [0002] In cases where a stator is formed by inserting a winding coil formed by winding wire into a slot formed in an inner peripheral face of a stator core, the winding coil is first formed in a winding jig. The winding coil is then temporarily shifted to an insertion jig and thereafter inserted so as to be positioned within the stator core. A winding device disclosed in a Patent Document 1 includes a flyer, which is equivalent to the aforementioned winding jig, rotatable and able to supply the wire, a winding frame on which the wire is wound by the flyer, and a blade for receiving the wire wound on the winding frame. Then, a unipolar coil is
15 formed by winding the wire by means of the flyer and the winding frame. The unipolar coil is sequentially dropped onto, i.e. received by, the blade so that a winding coil is formed by multiple unipolar coils. The blade that has received the winding coil is moved to a position facing a stator core, and a coil inserter, equivalent to the insertion jig, is moved so that the winding coil is inserted so as to be positioned within the stator core.

20 [0003] According to the ^{SUMMARY} aforementioned winding device, disclosed in the Patent Document 1, however, the blade holding the winding coil is moved to a position facing the stator core after the winding coil is formed. Therefore, ^{although} while the blade moves to a position facing the stator core so that the winding coil is inserted so as to be positioned within the stator core, and then returns to a position facing the flyer and the winding frame, a new winding coil, i.e. a
25 winding coil that is next to be inserted into the stator coil, cannot be formed. A standby time during which the flyer and the winding frame do not operate becomes long, and thus is not satisfactory in terms of reducing the time for manufacturing a stator.

[0004] Patent Document 1: Japanese Patent Application No. 2000-253631

DISCLOSURE OF INVENTION

30 OBJECT TO BE SOLVED BY THE INVENTION

[0005] The ^{disclosure addresses} present invention has been made in view of the above circumstances ^{by} and provides a stator manufacturing device that can bring a winding coil to be inserted into a

stator core and to be shaped, and at the same time, bring a new winding coil, which is next to be inserted into the stator core, to be formed.

~~MEANS TO SOLVE OBJECT~~

5 [0006] According to ^{one} ~~an~~ aspect of the present invention, a stator manufacturing device including a winding unit for forming a winding coil ^{made up} ~~consisting~~ of a plurality of unipolar coils formed by winding wire, an insertion unit for receiving the winding coil from the winding unit and inserting the winding coil into a stator core, a shaping unit for shaping an outline of the winding coil that has been inserted into the stator core, and a transfer unit that is movable towards the insertion unit and the shaping unit, ^{wherein} ~~characterized in that~~, in a state of holding the stator core, the transfer unit, by relatively moving to the insertion unit, moves the winding coil into a position for insertion into the stator core, and, by relatively moving to the shaping unit, forms an outline of the winding coil.

15 [0007] The stator manufacturing device ~~according to the present invention~~ includes the winding unit, the insertion unit, and the shaping unit formed into a single unit. In addition, the stator manufacturing device includes the transfer unit ^{that is} ~~movable~~ towards the insertion unit and the shaping unit. Thus, the winding coil can be formed and then the outline of the winding coil positioned within the stator core can be shaped consistently in the stator manufacturing device. The space required for installing the stator manufacturing device can be reduced in comparison with cases where the aforementioned units are separately installed.

20 [0008] Further, ^{with} ~~according to~~ the stator manufacturing device, ~~of the present invention~~, the stator core is moved by the transfer unit so as to face the insertion unit and the shaping unit. Then, the winding coil is inserted into the stator core by a relative movement between the transfer unit and the insertion unit. In the same way, the winding coil positioned within the stator core is shaped by a relative movement between the transfer unit and the shaping unit.

25 [0009] ^{As a result, with} ~~Effects according to the stator manufacturing device of the present invention can be explained as follows.~~ According to the stator manufacturing device, first, the winding coil consisting of multiple unipolar coils, ~~that is~~ ^{that is} formed by winding a wire is formed in the winding unit. Then, the winding coil formed by multiple unipolar coils is ^{passed} ~~handed over~~ from the winding unit to the insertion unit by means of a relative movement between the winding unit and the insertion unit. While the winding coil is being formed or ^{passed} ~~handed over~~, the transfer unit can be in a standby state while holding the stator core.

[0010] Next, the transfer unit holding the stator core is moved towards the insertion unit that holds the winding coil. The transfer unit and the insertion unit are moved relative to each

other so that the stator core, held at the insertion unit, is inserted into the stator core held at the transfer unit. Then, the transfer unit and the insertion unit are again moved relative to each other in such a way that the transfer unit in which the stator core has received the winding coil is moved towards the shaping unit.

5 [0011] Accordingly, the winding unit can form, independently and separately from the insertion unit, the winding coil formed by multiple unipolar coils. In addition, the insertion unit can receive the winding coil from the winding unit, and thereafter, by operating with the transfer unit, cause the winding coil to be inserted into the stator core. Therefore, after the winding coil has been handed over to the insertion unit from the winding unit, ~~even while~~, ^{even while} by means of the transfer unit and the insertion unit, the winding coil is inserted ~~so as~~ to be positioned within the stator core, the winding unit can start forming a new winding coil that is to be next inserted into the stator core.

[0012] Next, the transfer unit holding the stator core, within which the winding coil is positioned, is moved towards the shaping unit, and the outline of the winding coil positioned within the stator core is shaped by a relative movement between the transfer unit and the shaping unit. Even while the transfer unit is moving, the winding unit can keep forming a new winding coil to be next inserted into the stator core, and the outline of the winding coil positioned within the stator core is shaped by means of the transfer unit and the shaping unit.

[0013] Therefore, ^{with} ~~according to~~ the stator manufacturing device ~~of the present invention, an~~ insertion of the winding coil into the stator core and shaping of the outline of the winding coil positioned within the stator core, and, ~~at the same time~~, forming of a new winding coil, which is to be next inserted into the stator core, are simultaneously performed. ^{as a result,} The time required for manufacturing the stator ^{can} ~~may~~ be reduced accordingly.

[0014] After the shaping of the outline of the winding coil is completed, the transfer unit can be moved towards the insertion unit while holding the stator core and, by a relative movement to the insertion unit, receive the winding coil. Then, depending on a specification of the stator to be formed, the winding coil can be repeatedly formed in the winding unit. The transfer unit can operate with the insertion unit and the shaping unit for repeatedly performing the insertion of the winding coil into the stator core and for shaping the outline of the winding coil.

BRIEF DESCRIPTION OF DRAWINGS ^{Center}

[0015] Fig. 1 is a perspective view of a stator manufacturing device according to an ^{embodiment} ~~of the present invention~~, ^{exemplary}

The disclosure will be made with reference to the drawings, in which:

Fig. 2 is a plane view of the stator manufacturing device according to the ^{exemplary} ~~embodiment of the present invention;~~

Fig. 3 is a perspective view of a winding unit according to the ^{exemplary} ~~embodiment of the present invention;~~

5 Fig. 4 is a plane view showing a state in which a winding coil is formed in the winding unit according to the ^{exemplary} ~~embodiment of the present invention;~~

Fig. 5 is a view of the winding coil formed by multiple unipolar coils according to the ^{exemplary} ~~embodiment of the present invention;~~

10 Fig. 6 is a plane view showing a state in which the winding unit holding the winding coil is made to approach an insertion unit;

Fig. 7 is a side view showing a state before the winding unit holding the winding coil is ^{brought} ~~made~~ close to the insertion unit;

Fig. 8 is a side view showing a state in which the winding unit holding the winding coil has been made to approach the insertion unit and been handed over to the insertion unit;

15 Fig. 9 is a side view showing a state in which a transfer unit holding a stator core is made to approach the insertion unit holding the winding coil;

Fig. 10 is a side view showing a state in which the winding coil is shifted from the insertion unit to be positioned within the stator core held at the transfer unit;

20 Fig. 11 is a plane view showing a state in which coil receiving portions of the insertion unit face slots formed on the stator core held at the transfer unit;

Fig. 12 is a side view showing a state in which a shaping unit shapes the winding coil positioned within the stator core held at the transfer unit;

Fig. 13 is a perspective view of the stator manufacturing device in a state in which the transfer unit has moved to a position facing the insertion unit;

25 Fig. 14 is a perspective view of the stator manufacturing device in a state in which the transfer unit is made to approach the insertion unit;

Fig. 15 is a perspective view of the stator manufacturing device in a state in which the transfer unit has moved from the position facing the insertion unit to a position facing the shaping unit;

30 Fig. 16 is a perspective view of the stator manufacturing device in a state in which the transfer unit approaches the shaping unit;

Fig. 17 is a perspective view of the stator manufacturing device in a state in which the transfer unit moves away from the shaping unit;

Fig. 18 is a perspective view of the stator manufacturing device in a state in which the transfer unit transports the stator to a transfer conveyer;

Fig. 19 is a perspective view of the stator manufacturing device in which the transfer conveyer transports the stator to the following process;

5 Fig. 20 is a plane view of a stator for a three-phase motor formed by a three-phase winding coil positioned within the stator core; and

Fig. 21 is a cross-sectional view of the stator for a three-phase motor formed by the three-phase winding coil positioned within the stator core.

~~BEST MODE FOR CARRYING OUT THE INVENTION~~ **DESCRIPTION OF THE PREFERRED EMBODIMENT**

10 [0016] A preferred embodiment of the present invention is explained below. According to the stator manufacturing device, ~~of the present invention~~, by repeating the forming, inserting, and shaping of the winding coil as required, a stator for a three-phase motor, which is obtained by the winding coil of a U-phase, a V-phase, and a W-phase positioned within the stator core, can be manufactured within a short period of time.

15 [0017] In addition, when the winding coil is moved into a position for insertion into the stator core, the transfer unit, in a state of holding the stator core, is preferably ~~constituted~~ ^{structured} to approach the insertion unit in a state where the insertion unit is holding the winding coil. In these circumstances, the position for inserting the winding coil into the stator core can be established by first fixing the insertion unit, and by then causing the transfer unit holding the stator core to approach. Thus, a structure of the stator manufacturing device can be ~~made~~ ^{simplified} simple.

20 [0018] Further, in a state of holding the stator core, the transfer unit is preferably ~~constituted~~ ^{structured} to approach the shaping unit at a time when the outline of the winding coil is being shaped. In these circumstances, shaping of the outline of the winding coil can be undertaken by first fixing the insertion unit, and by then causing the transfer unit holding the stator core ~~to~~ ^{to} approach. Thus, the structure of the stator manufacturing device is ~~thus~~ also ~~made~~ ^{simplified} simple.

25 [0019] Furthermore, the transfer unit includes a holding portion for holding the stator core and a swing arm for rotating the holding portion relative to a swing center axis. The insertion unit and the shaping unit are preferably arranged facing one another on a swing locus of the holding portion. In these circumstances, the transfer unit can move the stator core, held at the holding portion, to a position facing the insertion unit, and, by rotating the swing arm, also to a position facing the shaping unit. Therefore, the stator manufacturing device can be downsized and a structure thereof further simplified.

[0020] Furthermore, the winding unit preferably includes multiple coil winding frames, ^{coil winding frame} each for forming a unipolar coil formed by winding wire and each ^{coil winding frame} movably provided on a base holder. One of the multiple coil winding frames is made so as to protrude from the other ^{of the} coil winding frames, and an entire winding unit is rotated relative to the protruding coil

5 winding frame so that the unipolar coil is subsequently formed. In this case, a winding unit that can independently form the winding coil is easily provided separately from the insertion unit. Therefore, a structure of the stator manufacturing device can be further simplified. In addition, in this case, the unipolar coil can be subsequently formed on each coil winding frame by subsequently moving each coil winding frame for winding wire and making the coil
10 winding frame ~~to~~ protrude from the remaining coil winding frames so that a winding coil formed by multiple unipolar coils is formed.

~~DETAILED DESCRIPTION~~

[0021] ~~An embodiment of the present invention is explained with reference to the attached drawings.~~ As shown in Figs. 1 and 2, a stator manufacturing device 1, according to the present ^{embodiment}

15 embodiment includes a winding unit 2 for forming a winding coil 9 consisting of multiple unipolar coils 91 each formed by the winding of wire 90, an insertion unit 3 for receiving the winding coil 9 from the winding unit 2 and inserting the winding coil 9 into a stator core 81, a shaping unit 4 for shaping an outline of the winding coil 9 positioned within the stator core 81, and a transfer unit 5 movable to the insertion unit 3 and the shaping unit 4. The transfer
20 unit 5, with the stator core 81 held thereat, moves relative to the insertion unit 3 so as to bring the winding coil 9 to a position for insertion into the stator core 81. In addition, the transfer unit 5, with the stator core 81 held thereat, moves relative to the shaping unit 4 so as to shape the outline of the winding coil 9. A detailed explanation follows.

[0022] As shown in Figs. 1 and 2, the transfer unit 5 can carry the stator core 81 to the
25 insertion unit 3 and the shaping unit 4. The transfer unit 5 includes a holding portion 52 for holding the stator core 81, and a swing arm 51 for rotating the holding portion 52 relative to a swing center axis C4. Further, the transfer unit 5 includes a swing device (not shown) for rotating the swing arm 51. The insertion unit 3 and the shaping unit 4 are arranged so as to face one another on a swing locus S of the holding portion 52. By operating the swing device
30 for rotating the swing arm 51, the transfer unit 5 can carry the stator core 81 held ^{by} at the holding portion 52 to a position facing the insertion unit 3. The transfer unit 5 can also carry the stator core 81 to a position facing the shaping unit 4.

[0023] Further, as shown in Figs. 1 and 2, the holding portion 52 is ^{structured} ~~constituted so as~~ to hold an outer peripheral face of the stator core 81. The holding portion 52 includes a holding hole 521, formed on the swing arm 51, and a ^a clamp 522 movable in such a way that a size of the holding hole 521 is decreased. When the stator core 81 is inserted and positioned within the holding hole 521, the holding portion 52 can hold the stator core 81 in the holding hole 521 by operating the ^a clamp 522.

[0024] Furthermore, as shown in Figs. 1 and 2, the transfer unit 5 ^{not only} can rotate the holding portion 52 relative to the swing center axis C4 ^{but can also} ~~as well as~~ move the holding portion 52 in an axial direction L1 thereof. In other words, the swing arm 51 is rotatable, and slidable in the axial direction L1 ^{for} of the holding portion 52. ~~Then,~~ in a case where the winding coil 9 is inserted and positioned within the stator core 81, the swing arm 51 with the stator core 81 held thereat approaches the insertion unit 3 that holds the winding coil 9. In addition, ~~in a case where~~ ^{when} the outline of the winding coil 9 is shaped, the transfer unit 5 with the stator core 81 held thereat approaches the shaping unit 4.

[0025] According to the stator manufacturing device 1 ~~of the present embodiment,~~ the winding unit 2, the insertion unit 3, the shaping unit 4, and the transfer unit 5 are respectively arranged on a mounting 10. The stator manufacturing device 1 further includes a platform 11 where the stator core 81, into which the winding coil 9 has not yet been inserted, can be mounted, and a transfer conveyer 12 for transporting a stator 8, within which the winding coil 9 is positioned and shaped, to the outside of the stator manufacturing device 1. The transfer conveyer 12 includes a pallet 121 capable of accommodating and transporting the stator 8 manufactured in the stator manufacturing device 1.

[0026] The transfer unit 5 receives the stator core 81 in the holding portion 52 in a state in which the holding portion 52 is moved to face the platform 11. The transfer unit 5 also transports the stator 8 held at the holding portion 52 from the insertion unit 3, or the shaping unit 4, to the transfer conveyer 12.

[0027] According to the ^{embodiment} ~~present~~ embodiment, the swing center axis C4 of the transfer unit 5 is arranged on a substantially center portion of the mounting 10. Then, around the swing center axis C4, the platform 11, the winding unit 2, the insertion unit 3, the shaping unit 4, and the transfer conveyer 12 are arranged. By rotation of the swing arm 51 relative to the swing center axis C4, the stator core 81 held at the holding portion 52 is transported to respective positions facing the platform 11, the winding unit 2, the insertion unit 3, the shaping unit 4, and the transfer conveyer 12.

[0028] As shown in Figs. 3 and 4, the winding unit 2 includes a base holder 21 and multiple coil winding frames 22, each provided so as to be movable in a direction L2, relative to the base holder 21. That is, each coil winding frame 22 is able to approach or move away from, the base holder 21. The coil winding frame 22 is provided for forming the unipolar coil 91, by the winding of wire 90. In addition, multiple crossover winding frames 23 are respectively arranged between the coil winding frames 22 so as to connect the unipolar coils 91 to each other. Each crossover winding frame 23 is also movable in a direction approaching, or moving away from, the base holder 21.

[0029] The winding unit 2 forms a unipolar coil 91 such that one of the coil winding frames 22 is made to protrude away from the remaining coil winding frames 22 and the crossover winding frames 23. Thus, the unipolar coil 91 is formed by rotation of the entire winding unit 2 relative to the protruding coil winding frame 22. The respective coil winding frames 22 for winding the wire 90 are sequentially moved in the direction L2 and made to protrude away from the remaining coil winding frames 22 and the crossover winding frames 23. Thus, the unipolar coils 91 are sequentially formed on the respective coil winding frames 22 so that a winding coil 9, consisting of multiple unipolar coils 91, can be formed.

[0030] As shown in Figs. 3 and 4, the base holder 21 is movable relative to a swing base 20 arranged so as to be rotatable relative to a swing base center axis C2. The coil winding frames 22 and the crossover winding frames 23 are arranged on the base holder 21 such that respective winding axes C1 of the coil winding frames 22 and the crossover winding frames 23 are substantially in parallel to each other. At the same time, the respective winding axes C1 are substantially in parallel to the swing base center axis C2. The base holder 21 is constituted such that the respective coil winding frames 22 for winding the wire 90 subsequently approach the swing base center axis C2.

[0031] As shown in Figs. 3 and 4, the base holder 21 is arranged so as to be rotatable relative to a rotary center axis C3, which is formed in an offset position from the swing base center axis C2 such that the rotary center axis C3 and the swing base center axis C2 are substantially parallel to one another. The respective coil winding frames 22 and the crossover winding frames 23 are provided on the base holder 21 such that the respective winding axes C1 of the coil winding frames 22 and the crossover winding frames 23 are arranged on a virtual circular R represented with reference to the rotary center axis C3, as shown in Fig. 4.

By rotating the base holder 21 by a predetermined angle, the respective coil winding frames 22 and the crossover winding frames 23 for winding the wire 90 are subsequently brought substantially made close.

to the swing base center axis C2 so that the winding axis C1 of each coil winding frame 22, or ~~each~~ ^{substantially coincide} of crossover winding frame 23, ~~can~~ ^{match} to all intents and purposes with the swing base center axis C2.

[0032] As shown in Fig. 3, each coil winding frame 22 includes an inside winding frame portion 225 assembled to the base holder 21, and an outside winding frame portion 226

provided so as to face the inside winding frame portion 225. The outside winding frame portion 226 is movable between a winding position P1, as shown in Fig. 7, in which wire 90 has been wound, and a separation position P2, as shown in Fig. 8, in which a unipolar coil 91 formed by the winding of wire 90 is separated from the coil winding frame 22, so that a distance between the outside winding frame portion 226 and the inside winding frame portion 225 ~~can be~~ ^{is} reduced.

[0033] The insertion unit 3 ^{Figs. 7-10,} includes a pushing insertion core 31, for pushing the winding coil 9 into a position for insertion into slots 811 formed in a stator hole 810 ^(Fig. 11) of the stator core 81, as shown in Figs. 9 and 10, and multiple coil receiving portions 32 formed on an outer peripheral face of the pushing insertion core 31, and receiving unipolar coils 91 from each coil winding frame 22, as shown in Figs. 7 and 8.

[0034] As shown in Fig. 6, multiple guiding portions 33 are respectively arranged between the coil receiving portions 32 in such a way that each guiding portion 33 is formed in a direction substantially identical to that in which the coil receiving portion 32 is formed. The respective guiding portions 33, as shown in Fig. 11, face teeth 812 that are respectively formed between the slots 811 of the stator core 81, so as to guide each unipolar coil 91 of the winding coil 9 into a position for insertion into the slots 811. Further, by a single ~~relative~~ movement relative to the winding unit 2, the insertion unit 3 can receive the winding coil 9 formed in the winding unit 2 consisting of multiple unipolar coils 91.

[0035] As shown in Figs. 7 and 8, according to the ~~present~~ ^{embodiment}, the winding unit 2 and the insertion unit 3 are provided so as to face one another in the stator manufacturing device 1. In addition, the winding unit 2 is movable relative to the insertion unit 3. ^W Then, the winding unit 2 is made to approach the insertion unit 3, and the outside winding frame portion 226 is moved from the winding position P1 to the separation position P2, ~~so that~~ ^{so that} the winding coil 9 can be accepted from the winding unit 2 into the insertion unit 3.

[0036] The shaping unit 4 includes a main body portion 41 to be inserted into the stator hole 810 (see Fig. 11) of the stator core 81, and movable shaping portion 42 that, by moving in an outer peripheral direction D1 of the main body portion 41, as shown in Fig. 12, shapes

the outline of the winding coil 9 positioned within the stator core 81. In a case where the transfer unit 5 ~~is made to~~ approach ^{to} the shaping unit 4, and then the main body portion 41 of the shaping unit 4 is inserted into the stator hole 810 of the stator core 81, the winding coil 9 positioned within the stator core 81 can be shaped by moving the movable shaping portion 42 in the outer peripheral direction D1 of the main body portion 41. The stator hole 810 is a hole used when a rotor is provided for the stator 8.

[0037] As shown in Fig. 10, in ~~a~~ ^{the} case where the winding coil 9 is inserted into the stator core 81, a part of the unipolar coil 91 of the winding coil 9 protrudes from ~~an~~ ^{each} axial end portion 813 of the stator core 81 and forms a coil end portion 93. Then, as shown in Fig. 12, in a shaping process ^{for} of the winding coil 9 in which the transfer unit 5 and the shaping unit 4 are used, ~~the~~ ^{each} coil end portion 93 is shaped so as to be deformed and move in the outer peripheral direction D1 of the stator core 81.

[0038] Next, an explanation follows of a method for manufacturing the stator 8 by providing the winding coil 9 within the stator core 81 according to the aforementioned stator manufacturing device 1. According to the ~~present~~ ^{exemplary} embodiment, the stator 8 is formed through a winding process, a handing process, an inserting process, and a shaping process. First, in the winding process, as shown in Fig. 5, by use of the winding unit 2, the winding coil 9 ~~consisting~~ ^{made up} of multiple unipolar coils 91 is formed by winding wire 90 into a loop shape. In the winding process, as shown in Figs. 3 and 4, the base holder 21 is rotated at a predetermined angle relative to the rotary center axis C3 so that the winding axis C1 of the coil winding frame 22, or of the crossover winding frame 23, which is used for winding the wire 90, substantially ^{coincides} matches with the swing base center axis C2.

[0039] Then, as shown in Fig. 3, the coil winding frame 22, or the crossover winding frame 23, used for winding the wire 90 is made to protrude away from the remaining coil winding frames 22 and the crossover winding frames 23. When the swing base 20 is rotated relative to the swing base center axis C2, the entire winding unit 2 can be rotated relative to the winding axis C1 of the protruding coil winding frame 22, or of the crossover winding frame 23. Thus, the wire 90 is wound on the protruding coil winding frame 22 or on the crossover winding frame 23, thereby forming a unipolar coil 91, or a crossover wire 92. In the same way, as shown in Fig. 4, a unipolar coil 91, or a crossover wire 92, is formed on the respective remaining coil winding frames 22 and the crossover winding frames 23 so that a winding coil 9 formed by unipolar coils 92 connected to one another by the respective crossover wires 92 is ^{produced} ~~acquired~~ (see Fig. 5).

[0040] Next, in the handing process, as shown in Figs. 6 to 8, the winding coil 9 formed ~~se~~^{by} ~~as to be wound in~~ the winding unit 2 is handed over to the insertion unit 3. In ~~this~~^{the} handing process, as shown in Figs. 7 and 8, the winding unit 2 is made to approach the insertion unit 3 so that each coil receiving portion 32 is inserted into a recess portion 221 formed so as to extend in the winding axis direction C1 of each coil winding frame 22 in the winding unit 2.

Then, as shown in Figs. 6 and 8, each of the coil winding frames 22 is connected to its corresponding coil receiving portion 32 so as to form a handover route 30 for handing over each of the unipolar coils 91.

[0041] In the aforementioned state, the outside winding frame portion 226 of each coil winding frame 22 is moved from the winding position P1 to the separation position P2. At the same time, a pushing core 211 movably provided within the base holder 21, is moved ^{in the direction of the arrow in Fig. 8} forward, thereby enabling the handing over of the winding coil 9, held at the coil winding frame 22, to the coil receiving portion 32 of the insertion unit 3. In addition, during the winding process and the handing process of the winding coil 9, as shown in Fig. 1, the holding portion 52 of the transfer unit 5 is moved to a position facing the platform 11. With the stator 81 held at the holding portion 52, the transfer unit 5 is kept on standby.

[0042] Next, in the inserting process, the winding coil 9, held at the insertion unit 3, is inserted ^{into and} so as to be positioned within the stator core 81 that is held ^{by} at the transfer unit 5, as shown in Figs. 9 to 11, 13, and 14. In the inserting process, the holding portion 52 of the transfer unit 5 is moved to a position facing the insertion unit 3 and then the swing arm 51 is made to approach the insertion unit 3.

[0043] Then, as shown in Figs. 9 and 11, the coil receiving portions 32 of the insertion unit 3 are respectively inserted into the stator holes 810 of the stator core 81 that is held at the holding portion 52 of the transfer unit 5. As shown in Fig. 10, the pushing insertion core 31 of the insertion unit 3 is made to approach the stator core 81 so that each unipolar coil 91 held at the coil receiving portion 32 is inserted into the slots 811 of the stator core 81 held at the holding portion 52 of the transfer unit 5. The winding coil 9 is accordingly from the insertion unit 3 inserted into the stator core 81. Further, after the winding coil 9 is positioned within the stator core 81, the coil end portion 93 ^{is} formed by a part of the unipolar coil 91 of the winding coil 9 protruding ^{that} from the axial end portion 813 of the stator core 81.

[0044] Next, in the shaping process, the outline of the winding coil 9 positioned within the stator core 81 is shaped as shown in Figs. 12, 15, and 16. In the shaping process, the holding portion 52 of the transfer unit 5 is moved to a position facing the shaping unit 4 as shown in

Fig. 15, and then the swing arm 51 is made to approach the shaping unit 4, as shown in Fig. 16. The main body portion 41 and the movable shaping portion 42 of the shaping unit 4 are inserted so as to be positioned within the stator hole 810 of the stator core 81 held at the holding portion 52 of the transfer unit 5.

5 [0045] In a state in which the main body portion 41 and the movable shaping portion 42 are positioned within the stator hole 810, as shown in Fig. 12, the movable shaping portion 42 is moved in the outer peripheral direction D1 of the main body portion 41 so that, by means of the movable shaping portion 42, the coil end portion ^{5 or} 93 is deformed and made to move in the outer peripheral direction D1 of the stator core 81. Accordingly, the outline of the winding coil 9 positioned within the stator core 81 is shaped, and a new winding coil 9, which is newly formed in the winding unit 2, can be easily inserted into the slots 811 of the stator core 81 in such a manner that the newly formed winding coil 9 overlaps the winding coil 9 previously formed from an inner peripheral side thereof.

10 [0046] After the shaping process, the transfer unit 5, once again holding the stator core 81, can be moved to a position facing the insertion unit 3 and, by moving relative to the insertion unit 3, receive the newly formed winding coil 9. In accordance with a specification of the stator 8 to be formed, the stator manufacturing device 1 can form the winding coil 9 repeatedly in the winding unit 2. The transfer unit 5 can bring the winding coil 9 to a position for insertion into the stator core 81 and shape the winding coil 9 repeatedly.

20 [0047] As shown in Figs. 17 and 18, the stator 8 manufactured in the stator manufacturing device 1 is transported by the transfer unit 5 to the pallet 121 of the transfer conveyer 12. Then, as shown in Fig. 19, by moving the pallet 121, the stator 8 can be transported to the next process of the stator manufacturing device 1. According to the ^{example} ~~present~~ embodiment, wire 90 for forming the winding coil 9 is formed by tying together multiple wires 901 (see Figs. 3 and 7).

25 [0048] According to the stator manufacturing device 1 of the ^{example} ~~present~~ embodiment, the stator 8 for a three-phase motor ~~manufactured~~ is obtained by inserting into the stator core 81 a winding coil 9 having three phases, a U-phase, a V-phase, and a W-phase, and by repeating the winding process, the handing process, the inserting process, and the shaping process. In more precise terms, a U-phase winding coil 9U is formed by means of a winding process and then inserted into the stator core 81 by means of the handing process and the inserting process. In addition, by means of the shaping process, the coil end portion 93 of the U-phase

30

winding coil 9U positioned within the stator core 81 is deformed and moved in the outer peripheral direction D1 of the stator core 81.

[0049] While the U-phase winding coil 9U is subjected to the handing process, the inserting process, and the shaping process, a V-phase winding coil 9V is formed during the winding process. Then, the V-phase winding coil 9V is inserted into the stator core 81 by

means of the handing process and the inserting process, and then, by means of the shaping process, the coil end portion 93 of the V-phase winding coil 9V positioned within the stator core 81 is deformed and moves in the outer peripheral direction D1 of the stator core 81.

[0050] While the V-phase winding coil 9V is subjected to the handing process, the inserting process, and the shaping process, a W-phase winding coil 9W is formed during the winding process. Then, the W-phase winding coil 9W is inserted into the stator core 81 by means of the handing process and the inserting process. The three-phase winding coil 9 of a U-phase, a V-phase, and a W-phase is positioned within the stator core 81 and a stator 8 for a three-phase motor is manufactured.

[0051] In the winding unit 2, each U-phase, V-phase, and W-phase winding coil 9 may be formed in multiple stages of implementation. In this case, after the winding coil 9, which is formed over multiple stages, is handed over to the insertion unit 3 after going through the winding and handing processes, the winding coil 9 can be inserted into the stator core 81 by means of the inserting process. In this case, the stator 8 for a three-phase motor can be also manufactured by means of the winding process, the handing process, the inserting process, and the shaping process.

[0052] As shown in Fig. 20, according to the stator 8 manufactured in the aforementioned manner, each U-phase, V-phase and W-phase winding coil 9 is inserted into the stator core 81 in an offset position through a predetermined number of slots 811 in a circumferential direction D2 of the stator core 81. In addition, as shown in Fig. 21, the respective coil end portions 93 protruding from the axial end portion 813 of the stator core 81 are arranged in the stator core 81 such that the V-phase coil end portion 93 overlaps with an inner peripheral side of the U-phase coil end portion 93 while the V-phase coil end portion 93 overlaps with an inner peripheral side of the W-phase coil end portion 93.

[0053] According to the stator manufacturing device 1 of the present exemplary embodiment, the platform 11, the winding unit 2, the insertion unit 3, the shaping unit 4, and the transfer conveyer 12 are integrally arranged on the mounting 10. Further, the transfer unit 5 that can move the holding portion 52 for holding the stator core 81 is provided on the mounting 10.

Thus, the winding coil 9 of each phase can be formed and, at the same time, inserted into the stator core 81, thereby consistently manufacturing the stator 8 in the stator manufacturing device 1. The space required for installation of the stator manufacturing device 1 can be reduced in comparison with cases where the units 2 to 5 are separately installed.

5 [0054] Further, according to the aforementioned stator manufacturing device 1, the transfer unit 5 moves the stator core 81 to the insertion unit 3 and the shaping unit 4. Then, the transfer unit 5 is made to approach the insertion unit 3 so that the winding coil 9 can be inserted into the stator core 81. The transfer unit 5 is made to approach the shaping unit 4 so that the winding coil 9 positioned within the stator core 81 can be shaped. Thus, according to
10 the aforementioned stator manufacturing device 1, by means of a transfer unit 5 that can operate with the insertion unit 3 and the shaping unit 4 while holding the stator core 81, the stator 8 can be manufactured within a reduced period of time.

[0055] Furthermore, the winding unit 2 can form, independently from the insertion unit 3, a winding coil 9 consisting of multiple unipolar coils 91. In addition, the insertion unit 3 can
15 receive the winding coil 9 from the winding unit 2 and thereafter, by operating with the transfer unit 5, cause the winding coil 9 to be inserted into the stator core 81.

[0056] Therefore, after the winding coil 9 is handed over from the winding unit 2 to the insertion unit 3, even while the insertion process is being conducted by the transfer unit 5 and the insertion unit 3, the winding unit 2 can start forming a new winding coil 9 to be inserted
20 next ~~time~~ into the stator core 81 by means of the winding process. In addition, the winding unit 2 can continue to form the new winding coil 9 while the transfer unit 5 is moving, or while the shaping process is being conducted by the transfer unit 5 and the shaping unit 4.

[0057] According to the stator manufacturing device 1 of the ^{exemplary} ~~present~~ embodiment, the winding coil 9 can be inserted into the stator core 81 and shaped while a new winding coil 9 is
25 being formed to be inserted into the stator core 81, thereby reducing ^{the} ~~time~~ for manufacturing the stator 8.